

D_SEGNI™



SMOKE & DOUBLE DIAMOND




Encaustic-look tiles with solid and decorative designs ranging from **geometrical, vintage and metropolitan patterns** to mix and match

D_SEGNI™

GLAZED PORCELAIN

REVEAL IMAGING®


FLOOR TILE



DS08 Chalk



DS09 Sand




DS10 Smoke



DS11 Mud



DS12 Denim



DS13 Shadow



DS14 Midnight


DECO TILE




MOUF Stella (4 Pieces)
Chalk/Mud Blend




MOUA Stella (4 Pieces)
Chalk/Midnight/Shadow/
Smoke Blend



MOUG Plaid (4 Pieces)
Chalk/Mud/Midnight/
Sand Blend




MOUC Plaid (4 Pieces)
Chalk/Midnight/Shadow/
Smoke Blend




MOUH Kaleido (4 Pieces)
Chalk/Mud/Smoke/
Midnight/Sand Blend




MOUD Kaleido (4 Pieces)
Chalk/Midnight/Shadow/
Smoke Blend




MOUJ Birdseye (4 Pieces)
Chalk/Mud/Midnight/
Sand Blend



MOUE Birdseye (4 Pieces)
Chalk/Midnight/Shadow/
Smoke/Denim Blend



MOUS Starlit (4 Pieces)
Chalk/Mud/Midnight/
Sand Blend



MOUN Starlit (4 Pieces)
Chalk/Midnight/
Shadow/Smoke Blend



MOUQ Parisian (4 Pieces)
Chalk/Mud/Midnight/
Sand Blend



MOUL Parisian (4 Pieces)
Chalk/Midnight/Shadow/
Smoke Blend



MOUR Peak (4 Pieces)
Chalk/Mud/Smoke/
Midnight/Sand Blend



MOUM Peak (4 Pieces)
Chalk/Midnight/Shadow/
Smoke/Denim Blend



MOUP Double Diamond
(4 Pieces) Chalk/Mud/
Midnight/Sand Blend





MOUK Double Diamond
(4 Pieces) Chalk/Midnight/
Shadow/Smoke Blend

USAGE

Floors	Walls	Countertops
F	W	C

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	8 x 8 Floor Tile	(7-7/8" x 7-7/8") (20.00 cm x 20.00 cm)	3/8"	10.32	24
	8 x 8 Deco Tile	(7-7/8" x 7-7/8") (20.00 cm x 20.00 cm)	3/8"	---	24

APPLICATIONS


	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit marazzitile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16"	 Medium Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Use of a latex modified thin-set is recommended for installation. For more information visit marazzitile.com.



Floor Tile



Wall Tile



Reveal Imaging®

Pre-Consumer
Recycled ContentCERTIFIED
PORCELAIN
TILE

All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.