

STONE AGE™

GLAZED CERAMIC

REVEAL IMAGING®

FLOOR TILE



Sequoyah



Lost Sea



Mammoth



Lava River

2 x 2 MOSAIC 12 x 12 SHEET



Sequoyah



Lost Sea



Mammoth



Lava River

USAGE




Floors	Walls	Countertops
F	W	C

FLOOR TILE



LOST SEA

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	18 x 18 Floor Tile	(17-1/2" x 17-1/2") (44.45 cm x 44.45 cm)	3/8"	15.26	7
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	14.53	15
	2 x 2 Mosaic (Mesh-mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm)	5/16"	---	10

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	■*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■*

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit marazzitile.com/DCOF.

APPLICATION NOTES:


Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.
*Mosaic tile only.

	Floor Tile		Deco	Trim
	18 x 18	12 x 12	2 x 2 Mosaic 12 x 12 Sheet	3 x 12 Floor Bullnose
Lava River	UL84	UL7Y	ULCK	UL88
Lost Sea	UL85	UL7Z	ULCL	UL89
Mammoth	UL86	UL82	ULCM	UL8A
Sequoyah	UL87	UL83	ULCN	UL8B

TRIM

Description	Size	Shape
Floor Bullnose	3 x 12	

INSTALLATION

Grout Joint Recommendation	Shade Variation
<p>Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order.)</p> <p>Mosaic: 1/8"</p>	 Medium Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor/Mosaic Result
Water Absorption	C373	< 7%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	IV

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A1371 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

FLOOR TILE



Floor Tile



Wall Tile



Reveal Imaging®



Pre-Consumer
Recycled Content



All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.