

METHOD™
COLORBODY™ PORCELAIN





Photo features Method Taupe Technique 24 x 24 Polished on the floor with Taupe Technique 24 x 24 Unpolished and 12 x 24 Textured on the fireplace.


Method™ by American Olean® pays homage to the design process with colors, sizes and finishes that flow seamlessly from interior to exterior spaces. A neutral, yet rich color palette provides the backdrop for fluid movement and graceful visual detail. The line includes six design-inspired colors and three finishes, all offered in large popular sizes with TruEdge™ rectified edges.

COLORBODY™ PORCELAIN FLOOR TILE - UNPOLISHED



STRUCTURE CREAM MT01 PROCESS BEIGE MT02 TAUPE TECHNIQUE MT04 KHAKI APPROACH MT05 STRATEGIC BROWN MT03 SYSTEM SABLE MT06

COLORBODY™ PORCELAIN FLOOR TILE - POLISHED



STRUCTURE CREAM MT01 PROCESS BEIGE MT02 TAUPE TECHNIQUE MT04 KHAKI APPROACH MT05 STRATEGIC BROWN MT03 SYSTEM SABLE MT06

COLORBODY™ PORCELAIN FLOOR TILE - TEXTURED





STRUCTURE CREAM MT01 PROCESS BEIGE MT02 TAUPE TECHNIQUE MT04 KHAKI APPROACH MT05 STRATEGIC BROWN MT03 SYSTEM SABLE MT06



Photo features Method™ Taupe Technique 12 x 24 Textured on the floor.

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	24 x 24 Floor Tile *	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	3/8"	15.20	4
	12 x 24 Floor Tile *	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	3/8"	15.12	8

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	S-43C9	30
	Cove Base	6 x 12	S-36C9	20
	Cove Base Corner	6 x 1	SC-36C9	10

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

* Modular sizes

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)

RELATIVE PRICING: High

SHADE VARIATION



HIGH
(V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●*
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	●**
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, refer to p. 294.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

* Unpolished and textured finishes only

** Textured finish only

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" on p. 293.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values <0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

For information on Test Results & Classifications, see p. 294.

For Installation Considerations, Care & Maintenance information, see pp. 295-297.