

ROSENDAL™
COLORBODY™ PORCELAIN



Photo features Rosendal Midtown Beige 6 x 36 on the floor and Entourage™ Alair™ Honey 2 x 4 Linear Hexagon mosaic on the wall.

A contemporary take on the popular wood-look tile trend, Rosendal™ by American Olean® pulls its inspiration from the clean lines and understated elegance of Scandinavian wood. Soft linear grain runs the length of each piece for visual richness, while a neutral color palette provides a crisp, contemporary aesthetic. Available in two linear sizes, Rosendal adds modern appeal to commercial and residential designs alike.

COLORBODY™ PORCELAIN FLOOR TILE



ALABASTER MOTIF RD12



METRO GRAY RD13



MIDTOWN BEIGE RD14





URBAN MOCHA RD11



Photo features Rosendal™ Urban Mocha 6 x 36 on the floor and Bricktown™ Cashmere Court 2 x 8 on the wall.

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	9 x 36 Floor Tile	8-7/8" x 35-1/4" (22.50 cm x 89.50 cm)	3/8"	13.02	6
	6 x 36 Floor Tile	5-3/4" x 35-1/4" (14.70 cm x 89.50 cm)	3/8"	12.69	9

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 1/8" (3/16" when installed in a staggered brick-joint pattern; overlap should not exceed 33%.)

RELATIVE PRICING: Medium to High

SHADE VARIATION



MEDIUM
(V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit refer to p. 294.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" on p. 293.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

For information on Test Results & Classifications, see p. 294.

For Installation Considerations, Care & Maintenance information, see pp. 295-297.