

INFUSION™
COLORBODY™ PORCELAIN



Photo features Infusion White Wenge and Gray Wenge 12 x 24 on the floor.

Your unique vision will come to life with Infusion™, using modular tiles that promote patterns using multiple sizes. Create seamless spaces and minimize grout joints with Infusion's full trim package and rectified edges featuring TruEdge™ technology. Versatile design will take the stage with a supporting cast of revered durability and modern style that can be used on the floor and wall.

COLORBODY™ PORCELAIN FLOOR TILE - FABRIC



WHITE FABRIC IF50



BEIGE FABRIC IF51



TAUPE FABRIC IF52



GOLD FABRIC IF53



BROWN FABRIC IF54



GRAY FABRIC IF55



BLACK FABRIC IF56

COLORBODY™ PORCELAIN FLOOR TILE - WENGE



WHITE WENGE IF60



BEIGE WENGE IF61



TAUPE WENGE IF62



GOLD WENGE IF63



BROWN WENGE IF64



GRAY WENGE IF65



BLACK WENGE IF66

DECORATIVE ACCENT



WHITE/BEIGE FABRIC IF80



TAUPE/BROWN FABRIC IF81



GOLD/TAUPE FABRIC IF82



GRAY/BLACK FABRIC IF83







All or select items within this series meet the requirements for these qualifications. For more information, refer to p. 304.



Photo features Infusion™ Gray Fabric 24 x 24, 6 x 24, 4 x 24, and 2 x 24 on the floor.

SIZES




			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	24 x 24 Floor Tile *▲	23-1/2" x 23-1/2" (59.80 cm x 59.80 cm)	3/8"	15.50	4
	12 x 24 Floor Tile *	11-3/4" x 23-1/2" (29.80 cm x 59.80 cm)	3/8"	11.69	6
	12 x 12 Floor Tile *▲	11-3/4" x 11-3/4" (29.80 cm x 29.80 cm)	3/8"	11.75	12
	6 x 24 Decorative Accent ▲	5-3/4" x 23-1/2" (14.60 cm x 59.80 cm)	3/8"	--	6

LINEAR EXPRESS™ SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	6 x 24 Floor Tile *▲	5-3/4" x 23-1/2" (14.60 cm x 59.80 cm)	3/8"	10.65	11
	4 x 24 Floor Tile *▲	3-13/16" x 23-1/2" (9.70 cm x 59.80 cm)	3/8"	6.46	10
	2 x 24 Floor Tile *▲	1-13/16" x 23-1/2" (4.70 cm x 59.80 cm)	3/8"	6.66	20

Additional linear and rectangular sizes available through Linear Express™, American Olean's linear cutting service. Visit americanolean.com/LinearExpress for size and order information.

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose ▲◆	4 x 12	S-44C9	30
	Cove Base ◆	6 x 12	S-36C9T	30
	Cove Base Outcorner ◆	6 x 1	SC-36C9T	15

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.
* Modular sizes ▲ Available in Fabric finish only ◆ Coordinates with both Fabric and Wenge floor tile

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)

RELATIVE PRICING: High

SHADE VARIATION



PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, refer to p. 294.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.
This product is directional by design. Direction of tile should be considered during installation.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" on p. 293.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

For information on Test Results & Classifications, see p. 294.
For Installation Considerations, Care & Maintenance information, see pp. 295-297.
For additional information on Linear Express™, see p. 282.