

Field Tile Sizes



Clay - CLA
CRDANTCLA848 - 8"x48" Matte



Walnut - WAL
CRDANTWAL848 - 8"x48" Matte



Wenge - WEN
CRDANTWEN848 - 8"x48" Matte



Clay - CLA
CRDANTCLA2424 - 24"x24" Matte



Walnut - WAL
CRDANTWAL2424 - 24"x24" Matte



Wenge - WEN
CRDANTWEN2424 - 24"x24" Matte



Photo Features 8"x48" Field Tile - Matte in Clay.





Antique

Glazed Color Body Porcelain


Photo Features 8"x48" Field Tile - Matte & 24"x24" Field Tile - Matte in Walnut.

SIZING & PACKAGING

| Type | Shape | Item Code | Size | Description | Pcs / Ctn | Sf / Ctn |
|-------|--|---------------|---------|--------------------|-----------|----------|
| Field |  | CRDANT***848 | 8"x48" | Field Tile - Matte | 4 | 10.12 |
| |  | CRDANT***2424 | 24"x24" | Field Tile - Matte | 3 | 11.63 |


ANSI TECHNICAL SPECIFICATIONS

| | DCOF Acutest | PEI Rating ASTM# C1027 | Frost Resistant ASTM# C1026 | Scratch Resistance MOHS | Breaking Strength ASTM# C648 | Water Absorption ASTM# C373 | Chemical Resistance ASTM# C650 |
|---------|-----------------|------------------------------|-----------------------------------|-------------------------------|------------------------------------|-----------------------------------|--------------------------------------|
| Results | ≥ 0.42 | Pass ≤ 175(ISO) | Unaffected | N/A | Pass (1,300 ISO) | ≤ 0.5% | Unaffected |




APPLICATIONS

| | Floors | Walls | Countertops | Shower Floors | Shower Walls | Pools/Spas |
|------------------|--------|-------|-------------|---------------|--------------|------------|
| Residential | ●† | ◻ | ◻ | ●† | ◻ | ◻ |
| Light Commercial | ●† | ◻ | ◻ | ●† | ◻ | ◻ |
| Commercial | ●† | ◻ | ◻ | ●† | ◻ | ◻ |



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ⊘ Applications & ANSI Technical Specifications do not apply
- * Special Order only



† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Minimum grout joint must be 3/16 inch. Please refer to the most current TCNA Handbook for installation guidelines. It is recommended to install 24"x24" deco field tiles in a diamond pattern without an offset. Use of a leveling system is strongly recommended.

Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field, mosaic, and trim tile may not be an exact match. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Check Manufacturer's specifications as some Mosaic tiles may not be appropriate for wet applications. Reference the most current TCNA Handbook, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance guide for installation, application, care and maintenance information. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make changes to product specifications at any time without notice. Please visit www.bedrosians.com for current product information.

MKTTERCARDANT