### Field Tile Sizes



White - WHI STPHIGWHI936\* - 9"x36" Rectified - Honed STPHIGWHI1224 - 12"x24" Pressed - Honed STPHIGWHI1224P\* - 12"x24" Rectified - Polished STPHIGWHI1836\* - 18"x36" Rectified - Honed



Beige - BEI STPHIGBEI936\* - 9"x36" Rectified - Honed STPHIGBEI1224\* - 12"x24" Pressed - Honed STPHIGBEI1224P\* - 12"x24" Rectified - Polished STPHIGBEI1836\* - 18"x36" Rectified - Honed



Cocoa - COC STPHIGCOC936\* - 9"x36" Rectified - Honed STPHIGCOC1224\* - 12"x24" Pressed - Honed STPHIGCOC1224P\* - 12"x24" Rectified - Polished STPHIGCOC1836\* - 18"x36" Rectified - Honed



Greige - GRE
STPHIGGRE936\* - 9"x36" Rectified - Honed
STPHIGGRE1224 - 12"x24" Pressed - Honed
STPHIGGRE1224P\* - 12"x24" Rectified - Polished
STPHIGGRE1836\* - 18"x36" Rectified - Honed



Dark Greige - DAG STPHIGDAG936\* - 9"x36" Rectified - Honed STPHIGDAG1224 - 12"x24" Pressed - Honed STPHIGDAG1224P\* - 12"x24" Rectified - Polished STPHIGDAG1836\* - 18"x36" Rectified - Honed



Black - BLA BIACK - BLA
STPHIGBLA936\* - 9"x36" Rectified - Honed
STPHIGBLA1224\* - 12"x24" Pressed - Honed
STPHIGBLA1224P\* - 12"x24" Rectified - Polished
STPHIGBLA1836\* - 18"x36" Rectified - Honed

# 2"x2" Mosaic - Honed (12"x12" Sheet)



White - WHI STPHIGWHI22MO




Beige - BEI STPHIGBEI22MO\*




Cocoa - COC



Greige - GRE STPHIGGRE22MO



Dark Greige - DAG STPHIGDAG22MO



Black - BLA STPHIGBLA22MO\*

# Herringbone Mosaic - Honed (12"x12" Sheet)



White - WHI STPHIGWHIHERMO\*



Beige - BEI STPHIGBEIHERMO\*



Cocoa - COC STPHIGCOCHERMO\*



Greige - GRE STPHIGGREHERMO\*



Dark Greige - DAG STPHIGDAGHERMO\*



Black - BLA STPHIGBLAHERMO\*



#### SIZING & PACKAGING

Туре	Shape		Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field			STPHIG•••936*	9"x36"	Rectified Field Tile - Honed	5	11.10
			STPHIG•••1224	12"x24"	Pressed Field Tile - Honed (DAG, GRE & WHI Colors Only)	8	15.75
	STPHIG		STPHIG•••1224*	12"x24"	Pressed Field Tile - Honed (BEI, BLA & COC Colors Only)	8	15.75
		Ø	STPHIG•••1224P*	12"x24"	Rectified Field Tile - Polished	8	15.75
			STPHIG•••1836*	18"x36"	Rectified Field Tile - Honed	5	22.19
Trim			STPHIG•••424BN	4"x24"	Bullnose - Honed	16	10.39
			STPHIG•••436BN*	4"x36"	Bullnose - Honed	16	15.78
		Ø	STPHIG ••• 612COVE*	6"x12"	Cove Base - Honed	8	3.88
Mosaic		Ø	STPHIG•••22MO	12"x12" Sheet	2"x2" Mosaic - Honed	10	-
		Ø	STPHIG•••HERMO*	12"x12" Sheet	Herringbone Mosaic - Honed	5	-

### ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	7	≥ 400 lbf	≤ 0.5%	Unaffected

### **APPLICATIONS**

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	•	•	•	•	•
Light Commercial	•	•	•	•	•	•
Commercial	•	•	•	•	•	•

### LEGEND

Product rated for Interior & Exterior use

Applications & ANSI Technical Specifications do not apply


- Product rated for Interior use only
  - \* Special Order only
- † May be suitable for Exterior Floors











Shade Variation

V2-Slight



Use of a leveling system during installation is strongly recommended

For installation of all polished, polished glazed, lappato, and honed porcelain/ceramic tiles, use a grout release prior to grouting to prevent absorption of the grout into the tile's micropores. Use a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the polished or honed tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet or exterior floor applications. Do not use acidic cleaners.

Minimum grout joint must be 3/16 inch. Please refer to the most current TCNA Handbook for installation guidelines.

Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field and trim tile may not be an exact match. We reserve the right to make changes to product specifications at any time without notice. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Prior to installation, installer must blend tiles from several different boxes to achieve an even distribution of color range. Installer must conduct a dry mock layout under proer lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Reference the most current TCNA Handbook, ANSI, manufacturer's specifications, and the Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, and/or use voids warranty. Please visit www.bedrosians.com for current product information.